



## DIMENSIONS

A	Overall length	5880mm
B	Length of flat bed	4770mm
C	Chassis cut-off to load centre	2240mm
D	Hook centre to end of equipment	580mm

## DIMENSIONS

E	Top of chassis to platform	360mm
Max R	Max radius of tele arms	3825mm
Min R	Min radius of tele arms	2600mm
	Overall width	2492mm

## CHASSIS

GVW	26 Tonne
Type	6x2 / 6x4

## CONTAINER

	Vol
Max capacity (open top)	22 cu yds
Max container width	2030mm

## EQUIPMENT CAPACITY

Lifting from ground level	
Arms fully retracted	15,500kg
Arms fully extended	10,800kg
Lifting 800mm below ground level	9,000kg
Typical Legal Payload	12,500kg

## STANDARD EQUIPMENT

- Independent telescopic arms
- Independent jack legs
- Air operated controls on 'Wander' lead
- Flat jack feet
- Access step & grab rail
- Lifting chains with dual position lugs
- 1 work lamp
- Full length bin guides
- Oil tank mounted to headboard

## OPTIONS

- Handbrake interlock
  - Rear view camera
  - Synchronised tele lift arms
  - Various chain options
  - Towing options
  - Fire extinguisher
  - Flashing warning beacon
  - First aid kit
  - Net box
  - Tool box
  - Chain covers
  - Various platform extensions
- Refer to E5496 for option details*

## EQUIPMENT DETAILS

Max operating pressure	340bar
Equipment weight	3400kg